



**FUSION
FOR
ENERGY**

SRF Linac for IFMIF DONES

Introduction

J. Creus Prats

F4E Market Survey
November 2025

Rev 2.0

1. DONES facility introduction
2. SRF Linac requirements
3. F4E scope for SRF Linac
4. SRF Linac design
5. Procurement schedule
6. F4E market research

- SRF linac is a key piece to achieve the goals of accelerating Deuterons for the high flux neutron test cell
- SRF linac hosts the superconducting RF cavities that accelerate the Deuteron beam
- SRF Linac is broken in 5 pieces to ease manufacturing, transport and operation.
- It's heavily reliant on: beamline, RF power system, cryogenics plant/distribution and vacuum system.

IDENTIFIED AS DONES WBS 6.5

- Acceleration from 5 to 40MeV
- D+ beamline at 125mA CW
- 175MHz Half Wave Resonator Cavities
 - Nb superconducting cavities cooled at 4.45K
 - External compression tuning system
 - Low Beta and High Beta Variants
 - 100kW LB and 200kW HB radio frequency power couplers
- 6T superconducting solenoid magnets + steerers


Cryomodule	CM1	CM2	CM3	CM4	CM5
HWR beta optimum	Low 0.116	Low 0.116	High 0.179	High 0.179	High 0.179
Elementary sequence	1 solenoid + 1 cavity	1 solenoid + 2 cavities	1 solenoid + 2 cavities	1 solenoid + 2 cavities	1 solenoid + 2 cavities
Number of elementary sequences	8	5	4	4	4
Inlet section	none	1 solenoid + 1 cavity	1 solenoid + 1 cavity	1 solenoid + 1 cavity	1 solenoid + 1 cavity
Total number of cavities	8	11	9	9	9
Total number of solenoids	8	6	5	5	5
Output energy (MeV)	8.3	13.9	21.3	30.3	40

- Outfitting of SRF testing facilities necessary for the project (coupler conditioning stand, adapt cryostat for cavity+coupler+tuner test)
- Critical components design, qualification and series production
 - Power couplers: 19x 100kW + 2 spares, 27x 200kW + 2 spares
 - Cavities: 19x LB + 2 spares, 27 HB + 2 spares
 - Solenoids: 29 units + 4 spares
 - Beam diagnostics: μ LM, BLM, BPM
- Manufacturing of 5 cryomodules and integration of critical components
- Local Instrumentation and Control System
- Beamline warm sections interconnecting cryomodules
- Transportation and rigging: Vibration absorption frame + delivery to DONES site
- Installation, Construction Completion Review and Site Acceptance Test

- **μLM:** Micro Loss Monitors.
With 3 units located in each solenoid, provide beam loss sensitivity helping beam fine tuning and to launch the MPS to protect the cold-mass components if losses exceed 1 W/m.
- **nBLM:** Beam Loss Monitors.
Interlock connection to the machine protection system with response required in less than 10 μs if losses exceed 1W/m.
- **BPM:** Beam Position Monitors
Button type beam position monitors with 4 pickups in each solenoid, operating at 4.45K
- Space in warm sections for future install of SEM grid in the warm sections.

Dimensions of cavity +RF coupler

Not represented: Tuner assembly, cryogenic, beam and vacuum interfaces



	Low Beta	High Beta
A	388	407
B	228	400
C	819	890
D	650	650
E	1029	1042

Dimensions in millimeters

F4E is evaluating the vendors in the market survey with the following categories:

Capabilities to work on a cryomodule full scope project

- Vendor internal resources: project managers and engineers
 - Capabilities beyond “build to print”
- Vendor existing scientific partners for such a project
- Production capacity to build 5 cryomodules

Capabilities of SRF testing beyond jacketed cavity acceptance tests

- Test with HB cavity + coupler + tuner
- RF coupler conditioning
- Full size cryomodule test

Specialized experience in the topics listed:

- Full cryomodule thermohydraulic design, mechanical design and integration
- Scientific partners
- Beam instrumentation
- Superconducting magnets
- RF power couplers

- F4E researching industry capabilities on the potential scope of supply presented in the market survey
- Scientific partners are key for design maturity of some components
- Aggressive schedule heavily dependent on the engineering resources and production capacity of the selected suppliers.